FAIL SAFE ELECTROHYDRAULIC UNIT IP67 FOR SAFE AREA		
MEHX		Basic composition
ACTUATOR		
XXX		Model of rack and pinion actuator (030, 040, 060, 100, 140, 200, 250, 370 & 500) *Higher torque available - Contact Radius*
	MOTOR POWER SUPPLY	
	XXXVAC	110/220/380 VAC Motor power supply
	XXXVDC	24 VDC Motor power supply
	CONTROLS POWER SUPPLY	
	BLANK	110VAC (Standard)
	24	24 VDC for control unit
	LOW PRESSURE	
	BLANK	Not required
	P1	With one safety pressure switch for checking the opening of the actuator
	HIGH PRESSURE	
	BLANK	Not required
	P2	With one safety pressure switch for high pressure relief in the unit
	TYPE OF CONTROL	
	BLANK	Not required
	RY	With programable relay for PST, STOP button and other options
	MOD	With 4-20mA signal for modulation
	LOCAL / REMOTE SELECTOR	
	BLANK	Not required
	S	With selector switch OPEN / CLOSE / REMOTE
	L	Local control unit with OPEN - CLOSE - REMOTE/LOCAL SELECTOR buttons
	LR	Local control unit for programmable relay or modular version with OPEN - CLOSE - STOP - PST - REMOTE / LOCAL SELECTOR buttons
	LIGHTS FOR LOCAL CONTROL	
	BLANK	Not required
	H	Lights for the local control unit
	MANUAL OVERRIDE	
	BLANK	Not required
	MH	With manual hand pump as manual override
	MO	With manual hand wheel as manual override
	OTHERS	
	BLANK	Not required
	YYY Others	Others

SIL3 Safety Integrity Level ⟨Ex⟩

PED approval

Radius LLC is ISO 9001:2008 certified.

Ex: MEHX-030-110VAC24-P1P2MOD-SH-MO